



SP11



SP11 scala fissa, particolarmente adatta ad un uso industriale, piattaforma standard mm 800x600, parapetto e corrimano da m 1,10. Progettata con la parte anteriore inclinata a 60° per una comoda salita. Su richiesta può essere prodotta anche con salita e discesa frontale, con inclinazione tra 30° e 45°. l'elemento di sostegno è dritto (90°), questo permette di avvicinarsi all'area di lavoro perfettamente.

SP11 fixed ladder, particularly suitable for industrial use, standard platform 800x600 mm, parapet and handrail 1.10 m. Designed with a 60° sloped front for comfortable climbing. On demand, it can also be produced with frontal descend, with an inclination between 30° and 45°. The supportive element is straight (90°), this allows to approach to the work area perfectly.


DI SERIE STANDARD



Optional

PARAPETTO

*Guardrail
possibilità di apertura
frontale o laterale
Front or side guardrail
opening*



GRADINO LARGO MM 165, CON INSERTI IN PVC, BLOCCATO TRAMITE VITI

*Flat step mm 165 with PVC
inserts, secured by screws*



POSIZIONI POSITIONS



DIMENSIONI SCALA

Ladder dimensions



CARICO COMPLESSIVO CONSENTITO

Total load permitted

Kg 150

CODICE	ART.	 n	 m	 m	 mm	 m	 Kg	€
 21420	SP11 04	4	2,10	0,97	1040	84x25 73x25	33,00	
 21421	SP11 05	5	2,30	1,20	1040	84x25 73x25	35,00	
 21422	SP11 06	6	2,55	1,45	1040	84x25 73x25	37,50	
 21423	SP11 07	7	2,80	1,70	1200	84x25 73x25	39,50	
 21424	SP11 08	8	3,05	1,95	1200	84x25 73x25	41,00	
 21425	SP11 09	9	3,30	2,20	1200	84x25 73x25	43,00	
 21426	SP 11 10	10	3,50	2,40	1200	84x25 73x25	44,50	
 21427	SP11 11	11	3,80	2,70	1200	84x25 73x25	49,00	
 21428	SP11 12	12	4,00	2,90	1200	84x25 73x25	51,50	
 21429	SP11 13	13	4,25	3,15	1200	84x25 73x25	54,00	

